

# Product datasheet

Specifications



Electronic overcurrent relay, EOCR,  
0.5 to 7A, 100-240 V, Overloaded  
with alarm and panel display meter,  
Hole type

EOCR3EZ-05AUH

## Main

|                              |                                                                                                                                                                                                                                                                                                                               |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product             | EOCR                                                                                                                                                                                                                                                                                                                          |
| Device short name            | EOCR-3EZ                                                                                                                                                                                                                                                                                                                      |
| Product or component type    | Protection relay                                                                                                                                                                                                                                                                                                              |
| Protection type              | Overload, $I_n > OC$ setting<br>Underload, $I_n < UC$ setting<br>Locked rotor for running, $I_n > 1.5...5$ times $OC$ setting<br>Sensitivity to phase loss<br>Earth fault, $I_g > I_g$ setting<br>Sensitivity to phase reverse<br>Locked rotor for starting, $I_n > 2...10$ times $OC$ setting<br>Phase unbalance, $5...50\%$ |
| Product specific application | Overload protection                                                                                                                                                                                                                                                                                                           |
| Network type                 | AC                                                                                                                                                                                                                                                                                                                            |
| Network frequency            | 50...60 Hz                                                                                                                                                                                                                                                                                                                    |
| Relay application            | Motor protection                                                                                                                                                                                                                                                                                                              |
| protection ajustment range   | 0.5...7 A                                                                                                                                                                                                                                                                                                                     |
| Tripping threshold           | 0.03...10 A (definite) - earth fault current                                                                                                                                                                                                                                                                                  |

## Complementary

|                                        |                                                                                                                                                                                        |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Us] rated supply voltage              | 100...240 V AC/DC                                                                                                                                                                      |
| Mounting support                       | Base unit: 35 mm DIN rail                                                                                                                                                              |
| Contacts type and composition          | 1 NC + 1 NO (OL)<br>1 NO (GR)                                                                                                                                                          |
| Short-circuit and overload protection  | By 4 A gG fuse                                                                                                                                                                         |
| [Ue] rated operational voltage         | 690 V AC 50...60 Hz for power circuit conforming to CSA<br>690 V AC 50...60 Hz for power circuit conforming to IEC 60947-4-1<br>600 V AC 50...60 Hz for power circuit conforming to UL |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947-4-1                                                                                                                                                       |
| Reset                                  | Manual reset<br>Electrical<br>Automatic reset                                                                                                                                          |
| Time delay type                        | O-Time: 0.2...120 s (definite)<br>Ed-Time: 0...30 s (definite)<br>E-Time: 0.05, 0.1...10 s (definite)                                                                                  |
| Display type                           | Bar graph<br>7 segments LED                                                                                                                                                            |
| power consumption per relay            | 5 W                                                                                                                                                                                    |
| Connections - terminals                | Control circuit: cable 2 x 1...1.5 mm <sup>2</sup> flexible with cable end - M3<br>Control circuit: cable 2 x 1...1.5 mm <sup>2</sup> flexible without cable end                       |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                   |                                                 |
|-------------------|-------------------------------------------------|
| Tightening torque | Control circuit: 0.8...1.2 N.m on cable, 4.7 mm |
| Height            | 56 mm                                           |
| Width             | 70 mm                                           |
| Depth             | 106 mm                                          |
| Product weight    | 470 g                                           |

## Environment

|                                             |                                                                                                                                                                                                                                                                                                                                                                                     |
|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards                                   | IEC 60947-4-1                                                                                                                                                                                                                                                                                                                                                                       |
| Product certifications                      | CE                                                                                                                                                                                                                                                                                                                                                                                  |
| IP degree of protection                     | IP20 conforming to IEC 60529                                                                                                                                                                                                                                                                                                                                                        |
| Ambient air temperature for operation       | -20...60 °C conforming to IEC 60947-4-1                                                                                                                                                                                                                                                                                                                                             |
| Ambient air temperature for storage         | -40...85 °C                                                                                                                                                                                                                                                                                                                                                                         |
| Operating altitude                          | 2000 m                                                                                                                                                                                                                                                                                                                                                                              |
| Fire resistance                             | 650 °C conforming to IEC 60695-2-12                                                                                                                                                                                                                                                                                                                                                 |
| Shock resistance                            | 15 gn for 11 ms conforming to IEC 60068-2-7                                                                                                                                                                                                                                                                                                                                         |
| Vibration resistance                        | 4 gn on panel mounting conforming to IEC 60068-2-6<br>2 gn on 35 mm DIN rail conforming to IEC 60068-2-6                                                                                                                                                                                                                                                                            |
| Dielectric strength                         | 2 kV 50...60 Hz in between case and circuit conforming to IEC 60255-5<br>1 kV 50...60 Hz in between contact conforming to IEC 60255-5<br>2 kV 50...60 Hz in between circuit conforming to IEC 60255-5                                                                                                                                                                               |
| Surge withstand                             | 6 kV conforming to IEC 61000-4-5                                                                                                                                                                                                                                                                                                                                                    |
| Electromagnetic compatibility               | Resistance to radiated electromagnetic fields: 10 V/m level 3 conforming to IEC 61000-4-3<br>Resistance to electrostatic discharge: 8 kV air, 6 kV contact conforming to IEC 61000-4-2<br>Resistance to fast transient: 2 kV conforming to IEC 61000-4-4<br>Conducted RF disturbances: 10 V conforming to EN 61000-4-6<br>Conducted RF disturbances: class A conforming to EN 55011 |
| [Ith] conventional free air thermal current | 3 A for control circuit                                                                                                                                                                                                                                                                                                                                                             |
| Permissible current                         | 100...240 V, 3 A AC/DC                                                                                                                                                                                                                                                                                                                                                              |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 5.6 cm  |
| Package 1 Width              | 7.0 cm  |
| Package 1 Length             | 10.6 cm |
| Package 1 Weight             | 470 g   |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

| Materials and Substances               |                                                                                        |
|----------------------------------------|----------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                    |
| Packaging without single use plastic   | No                                                                                     |
| SCIP Number                            | 440635ef-4ab9-4af3-beec-63d4c8a6a97d                                                   |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a>                                                 |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a> |

### Use Longer

| Lifetime extension |    |
|--------------------|----|
| Repair             | No |

### Use Again

| Repack and remanufacture |    |
|--------------------------|----|
| Take-back                | No |